Datasheet



M-1RA1

Sigfox 915 Antenna

CELLULAR

SIGFOX

The M-1RA1 is a Sigfox 915 Antenna with a wide band and high efficiency. It's an ideal solution for cellular IoT applications requiring a durable and cost-effective external antenna.

The M-1RA1 allows the antenna to be positioned for optimum performance compared to a fixed whip design. The antenna attaches with an SMA connector.



208 x 14 mm

www.miotsolutions.com

info@miotsolutions.com

Document Information

| Product | M-1RA1 |
|-------------|--------------------|
| Part Number | M-1RA1 |
| Description | Sigfox 915 Antenna |
| Version | 2.0 (current) |
| Date | 15-Sep-2023 |
| Status | Released |

Revision History

| Version | Date | Author | Changes |
|---------|--------------|----------|-----------------------|
| 1.0 | 16-Dec-2020 | Amy Li | Initial Release |
| 1.1 | 06-July-2023 | Hazel Xu | New layout and design |
| 2.0 | 15-Sep-2023 | Ivy Liao | New layout and design |



Product Overview

Product Description

The M-1RA1 is a Sigfox 915 Antenna with a wide band and high efficiency. It's an ideal solution for cellular IoT applications requiring a durable and cost-effective external antenna.

The hinged swivel design allows the antenna to be positioned for optimum performance and reduces the potential for damage from impact compared to a fixed blade design. The antenna attaches with an SMA plug (male pin) connector.

Key Features

- Operates in 900-930MHz
- Dual band antenna
- Vertical polarization
- High gain of 2.5dBi
- VSWR 1.7
- Omni-directional pattern

Applications

- Sigfox radios
- Gateways
- Set-Top Boxes
- Security
- Transportation
- Smart agriculture

Electrical Specifications

| Frequency | | | VSWR | Peak Gain | Efficiency |
|-----------|-----------|-----|------|-----------|------------|
| LORA | 900 - 930 | MHz | 1.7 | 2.5 d Bi | 40% |

| Frequency Ran | ge 900 – 930 MHz | Radiation Omnidirectional |
|---------------|------------------|--|
| Impedance | 50 Ω | Power Handling 50W |
| | | Capacity |
| Polarization | Vertical | Lighting Protection Direct Current earth |

Mechanical Specifications

| Cable Type | RG-178 | Enclosure | TPE |
|------------|-------------|-----------|-------|
| Dimensions | 208 x 14 mm | Color | Black |



| Connector | SMA | Material | PBT + PC |
|---------------|-----|----------|----------|
| (Termination) | | | |


Caution:

- 1. Do not apply excess mechanical stress to the component body or terminations. Do not attempt to re-form or bend the components, as this will cause damage to the component.
- 2. Do not expose the component to an open flame.
- 3. This specification applies to the functionality of the component as a single unit. Please ensure the component is thoroughly evaluated in the application circuit.

Product Image and Dimensions







Radiation Pattern


A radiation pattern is a graphical representation of the directional properties of an antenna. It shows how electromagnetic waves are distributed in space in relation to the direction of propagation.

By understanding the information provided by a radiation pattern, it is possible to optimize the design and performance of an antenna for specific applications.

XY Plane (H)

900 - 930 MHz






YZ Plane (E1)

900 – 930 MHz






YZ Plane (E2)

900 – 930 MHz







Antenna Smith and VSWR

| Frequency | VSWR | Freque | ency | VSWR |
|-----------|--------|--------|------|--------|
| 900 MHz | 1.3993 | 916 | MHz | 1.5585 |
| 915 MHz | 1.5463 | 930 | MHz | 1.7537 |










Antenna Efficiency and Gain

| Frequenc | Ξy | Efficiency | Gain |
|----------|-----|------------|------|
| 900 | MHz | 69% | 2.56 |
| 902 | MHz | 66% | 2.23 |
| 904 | MHz | 65% | 2.19 |
| 906 | MHz | 60% | 1.82 |
| 908 | MHz | 63% | 1.85 |
| 910 | MHz | 69% | 2.38 |
| 912 | MHz | 64% | 2.04 |
| 914 | MHz | 69% | 2.21 |

| Frequen | су | Efficiency | Gain |
|---------|-----|------------|------|
| 916 | MHz | 72% | 2.46 |
| 918 | MHz | 61% | 1.71 |
| 920 | MHz | 70% | 2.22 |
| 922 | MHz | 71% | 2.31 |
| 924 | MHz | 67% | 1.95 |
| 926 | MHz | 67% | 1.93 |
| 928 | MHz | 68% | 2.04 |
| 930 | MHz | 68% | 2.08 |
| | | | |









Environmental Data

| Operating Temperature | -40 °C to +85 °C |
|-----------------------|------------------|
| Compliance | RoHS |

Ordering Information

Product Variants

| Part Number | Description |
|-------------|--------------------|
| M-1RA1 | Sigfox 915 Antenna |



About MIOT

Miot Wireless Solutions, headquartered in Suzhou, China, was established in 2017. It has subsidiaries in Canada, the United States, Brazil, and EMEA. MIOT is a professional designer and manufacturer of Antennas and IoT PCBA products, providing turn-key service to customers

worldwide.

Our talented R&D team has experienced antenna, hardware, and software engineers who can participate in your new project, from something simple like antenna/selection and design, to complete turn-key services, which entails taking your concept and ideas through design, prototyping, debugging, certification, and manufacturing. Miot offers reliable products at

reasonable prices with fast delivery times to help you get ahead in the market.

Contact

MIOT Wireless Solutions Co. Ltd. 120-5800 Ambler Dr, MISSISSAUGA ONTARIO L4W 4J4 Canada

Website: www.miotsolutions.com

Email: info@miotsolutions.com

The information contained herein is provided "as is" and MOIT assumes no liability for using the information. No warranty, either express or implied, is given, including but not limited to the accuracy, correctness, reliability, and fitness for a particular purpose of the information. This document may be revised by MOIT at any time.

MIOT reserves all rights to this document and the information contained herein. Reproduction, use, modification, or disclosure to third parties of this document without express permission is strictly prohibited.

Copyright © 2023, MIOT Wireless Solutions Ltd. All Rights Reserved





